



# IP60-50 INTENSIFIER PUMP

## Construction

- Heavy gauge sheet metal covers
- Rugged all-steel welded framework
- All stainless steel fittings and components
- Hinged cover and removable access panels for convenient machine inspection and maintenance
- Integral hydraulic reservoir
- NEMA 12/13 rated electrical enclosure
- UL Certified electrical panel
- Optional sound insulation

## Standard Features

- High efficiency TEFC motor
- Electronically shifted intensifiers
- Wye-Delta motor starter assembly
- 1 quart (0.9 liter) high pressure attenuator
- Safety shutdown systems
- Automatic safety pressure bleed-down valve
- Integrated power distributor panel with disconnect
- Thermostatically controlled kidney loop cooling system
- Dual pressure set points
- Programmable Logic Controller (PLC) for operation and safety monitoring
- Axial piston, variable displacement, pressure-compensated hydraulic pump
- Hydraulic accumulator dampens pulsations
- Liquid filled pressure gauges
- UHP safety shielded tubing

## Optional Features

- CE Mark
- Advanced Controls

## Physical Size

- Length: 74 in (1880 mm)
- Width: 37 in (940 mm)
- Height: 53 in (1350 mm)
- Approximate Weight with Fluid: 2800 lbs. (1300 kg)

## Electric Motor

- Motor Output: 50 hp (37 kw)
- Motor Type: High Efficiency TEFC electric motor
- Full load amps @ 460vac (60Hz): 60
- Full load amps @ 230vac (60Hz): 120
- Full load amps @ 380vac (50Hz): 75

## Intensifier

- Type: Single piston, dual plunger, reciprocating
- Number of Intensifiers: one
- Continuous Operating Pressure: 55,000 psi (3800 bar)
- Intensification Ratio: 20:1
- UHP Flow Rate: 1.1 gpm (4.2 lpm)



## Low-Pressure Water/Intensification Water

- Type: Potable tap water
- \* Pretreated, <100 TDS, PH 6-8, Silica <15PPM
- Supply Requirements: 2 gpm (7.5 lpm) @ 60 psi (4 bar) min. / 70°F (21°C) max.
- Water Pre-filter to 0.45 Micron
- In-line UHP Water Filtration to 5 Micron

## Coolant Water

- Maximum Temperature: 70°F (21°C)
- Minimum: 2 gpm (7.5 lpm) @ Minimum 60 psi (4 bar)
- Heat Load: 39,000 BTU/hour minimum
- Heat Exchanger: Brazed Plate

## Hydraulics

- Reservoir Capacity: 35 gallons (135 liters)
- Filtration: 10 Micron

## Environmental

- Ambient Room Temperature: 50°-95°F (10°-35°C)
- Relative Humidity: Non-condensing, Maximum 95% @ 100°F



Specifications subject to change.

[www.jetedge.com](http://www.jetedge.com)  
+1-763-497-8700 | 1-800-JET-EDGE  
[sales@jetedge.com](mailto:sales@jetedge.com)